



**PELI**  
**BIOThermal™**



## MARKET LEADING SPACE EFFICIENCY AND PERFORMANCE FROM A REUSABLE BULK SHIPPER

### WHY CHOOSE CREDO VAULT?

- Reusable passive pallet shipper utilizing PCM Coolants
- 4 units per standard PMC pallet
- 4 way pallet entry with anti-slip entry
- 3 interchangeable temperature ranges; +2°C to +8°C, +15°C to +25°C, -20°C
- Built-in temperature monitor
- Single door access with 270° opening
- Lightweight & sturdy design
- Designed to be stackable for easy storage
- Integral viewing window for VIP monitoring
- Compatible with ISO and EURO pallet sizes

Available via the **Crēdo™ On Demand rental program**



**Duration - ISTA7D (min load)**  
144 hours chilled / ambient  
120 hours frozen

**Temperature Range**  
+2°C to +8°C chilled  
+15°C to +25°C ambient  
Below -20°C frozen

**Volume**  
1640L

**Tare Weight with coolants**  
880 lbs  
399 kg

**Internal Payload Height**  
51.2 in  
1300mm

**External Dimensions**  
57.20 x 47.09 x 61.97 in  
1453 x 1195 x 1574mm

FOR MORE INFORMATION ABOUT PELI BIOThermal PRODUCTS, PLEASE CONTACT:  
EMEA OFFICE - INFOEMEA@PELIBIOTHERMAL.COM T: +44 (0)1525 243 770  
AMERICAS OFFICE - INFOAMERICAS@PELIBIOTHERMAL.COM T: +(1)763 412-4800  
TOLL FREE US: T: +(877) 537-9800  
ASIA OFFICE - INFOASIA@PELIBIOTHERMAL.COM T: +65 6028 0252

PELIBIOTHERMAL.COM

ISO17025, ISO9001-2008 Accredited

Golden Hour™, TIC™, Crēdo™, Crēdo Cube™, Crdo ProEnvision™, Crdo Xtreme™, Crēdo Duracube™, Crēdo ProMed™, Sherpa Systems™, CoolGuard™ and CoolPall™ are registered trademarks of Pelican Products Inc., its subsidiaries and / or affiliates

2024 Peli BioThermal LLC all rights reserved



**PELI**  
**BIOThermal™**

**OUR PRIORITY-SAVING LIVES**