

INTRODUCING

Crēdo VAULT



At Peli BioThermal, we understand the challenges of maintaining product integrity, reducing costs, and gaining real-time visibility into shipments. Crēdo Vault™ addresses these needs by accommodating **four units per PMC**, supporting **multiple temperature ranges**, and being compatible with both **EU and ISO pallets**. Its lightweight, durable design optimizes space and reduces costs, while **IoT-enabled monitoring** provides real-time visibility for the secure delivery of temperature-sensitive products.

For further information, please contact your Peli BioThermal Account Manager

THERMAL RELIABILITY

ISTA 7D PROFILE (MIN LOAD)

144 hours • +2 °C to +8°C
• +15°C to +25°C

120 hours • Below -20°C

CONTAINER RELIABILITY

ISTA 7D PROFILE (MIN LOAD)

4 Units per standard PMC pallet
Way pallet entry with ant-tip

3 Interchangeable temperatures

DIMENSIONS & WEIGHT

TARE WEIGHT W/COOLANTS *

398
KG

880
LB

INTERNAL PAYLOAD HEIGHT *

1295
MM

51
IN

EXTERNAL DIMENSIONS

1453 x 1195 x 1574 MM
57.20 x 47.09 x 61.97 IN

*Subject to temperature range & manufacturing tolerances

